

## **AUX-MADI-COAX-DUAL**

64x64@96k Dual-Link MADI

Extension Card for FLX devices


User's Manual

**((en))**

## Table of Contents

1.	CONNECTORS.....	3
2.	DESCRIPTION.....	3
	2.1. Box Contents.....	3
3.	INSTALLATION.....	3
	3.1. Opening the flexiverter.....	3
	3.2. Flexiverter Inside View.....	4
	3.3. Installing the card.....	4
4.	DIP SETTINGS.....	5
5.	SELF-TEST.....	5
6.	SPECIFICATIONS.....	6
7.	APPENDIX.....	6
	7.1. Available AUX cards.....	6
	7.2. Available FLX devices.....	7
	7.3. Warranty.....	7
	7.4. Manufacturer contact.....	7
	7.5. Recycling.....	7
	7.6. Document Revision History.....	7
	7.7. About this document.....	8

## 1. CONNECTORS



- ① MADI coaxial input/output Link 1 (channels 1-64@48k / 1-32@96k / 1-16@192k)
- ② MADI coaxial input/output Link 2 (channels 33-64@96k / 17-32@192k)

## 2. DESCRIPTION

The AUX-MADI-COAX card provides 64x64 channels at 96k, or 32x32ch at 192k of MADI coaxial via MADI dual link<sup>1</sup>. It can be fitted into the **FLX-DANTE/SRC<sup>2</sup>** device to make a 64x64 channel 48k Dante < > 96k MADI converter.

For a detailed description of possible configurations, please refer to the manual of your base FLX device.

### 2.1. Box Contents

- 1 AUX-MADI-COAX-DUAL card
- 1 Slot cover plate
- This manual

## 3. INSTALLATION


### 3.1. Opening the flexiverter

- Required: Torx T10 screwdriver
- Power off the device and detach all cables to avoid short-circuit or damage
- Detach the device from the rack-mount kit


1 128ch @ 48k is supported by the card, but not yet by any of the FLX host devices. This functionality may be added later via firmware updates.

2 In any other FLX device, the card will act as AUX-MADI-COAX card, Link 2 is inactive.

- Remove the four top screws and the top cover by pulling it upwards:



### 3.2. Flexiverter Inside View













- ① Screws for AUX cover plate
- ② AUX card connector

### 3.3. Installing the card

- Remove the screws holding the cover plate, and the blank cover plate ①
- Insert the AUX card from inside, using the supplied cover plate. Make sure it is correctly fitted to the card connector ②
- Secure the card using two cover screws ①
- The card has been installed correctly if you are able to select an audio routing mode involving AUX (long-press MODE button to enter Route Mode Selection).

**4. DIP SETTINGS**




The behavior of the card can be controlled by DIP switches 4..6 on the FLX device. Changing the DIP settings will come immediately into effect.

<b>AUX-MADI-COAX</b> <b>AUX-MADI-COAX-DUAL</b>	 96k frame* <sup>3</sup>	  64ch output* <sup>3</sup>
	 48k frame <sup>3</sup>	  57ch (use for DiGiCo stagebox control) <sup>3</sup>
		  56ch output <sup>3</sup>
		  reserved

\* Default setting

**5. SELF-TEST**

The card can be tested for correct operation by the user. This is done using the self-test mode, in which a special random test pattern is output on all channels. This pattern is looped back via an external cable into the corresponding inputs, where it is checked for consistency.

- Connect "MADI Out" to the corresponding "MADI In" using a standard 75Ω impedance coaxial cable.
- Turn off the FLX, and hold down  button while switching on again
- Press  again until the "CLOCK" LEDs show "INT/48kHz" in  cyan color. The device is now in self-test mode.
- The "AUX" LED in the MODE sections shows the result of the self-test:
  -  red: error/no connection
  -  green (loopback data received ok)
- Press  again or power off the device to exit self-test mode.

<sup>3</sup> Applies to outputs only. Input format is always auto-detected, regardless of the switch setting

## 6. SPECIFICATIONS

Parameter	Value
Dimensions	118x80mm (WxH)
Weight	83g
Operating temperature	0.. +55°C, non-condensing
Storage temperature	-40.. +85°C, non-condensing
Cable lengths	Max. 70m. Use only 75Ω impedance coaxial cable
Channel count	64x64 @ 48kHz (56/57ch modes can be configured) NOTE: Dual-Link 128x128 @ 48kHz is not yet supported by any FLX firmware.  64x64 @ 96kHz (28ch mode can be configured) 16x16 @ 192kHz (14ch mode can be configured)
Sample rates	44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz
Latency	Interface < > Flexiverter internal: 2 samples

## 7. APPENDIX

### 7.1. Available AUX cards

At the time of writing (2025-02), the following AUX cards are available. More will come, please check [www.appsys.ch](http://www.appsys.ch) for updates.

Item	Description
AUX-ADAT	16x16ch ADAT I/O (2x Toslink In + 2x out). Supports also S/PDIF
AUX-AES3	8x8ch AES3 I/O on 1x DB25, fully transformer isolated
AUX-DANTE	64x64ch DANTE network card
AUX-MADI-COAX	64x64ch MADI for coaxial cable (BNC connectors)
AUX-MADI-COAX-DUAL	64x64ch@96k dual-Link MADI coaxial
AUX-MADI-OPTO	64x64ch MADI optical, SC connector (Multimode 125um 1310 nm)
AUX-MADI-SFP	64x64ch MADI for SFP (Small-Factor Pluggable) modules
AUX-MADI-SFP-DUAL	64x64ch@96k dual-Link MADI SFP
AUX-MADI-TP	64x64ch MADI-TP (Cat5) for DiGiCo, Soundcraft, Studer
AUX-MADI-SFP-DUAL	64x64ch@96k dual-Link MADI TP

## 7.2. Available FLX devices

At the time of writing (2025-02), the following FLX devices are available. More will come, please check [www.appsys.ch](http://www.appsys.ch) for updates.

Item	Description
FLX-AES3	16x16 channel AES3 flexiverter (with AUX slot)
FLX-AES3/SRC	16x16 channel AES3 flexiverter (with AUX slot) with 8 built-in, independent stereo SRCs on the AES3 inputs
FLX-AES50	96x96 channel AES50 flexiverter (with AUX slot)
FLX-DANTE	64x64 channel DANTE flexiverter (with AUX slot)
FLX-DANTE/SRC	64x64 channel DANTE flexiverter (with AUX slot) and built-in bi-directional 64x64ch Sample Rate Converter

## 7.3. Warranty

We offer a full two (2) year warranty from the date of purchase. Within this period, we repair or exchange your device free of charge in case of any defect\*. If you experience any problems, please contact us first. We try hard to solve your problem as soon as possible, even after the warranty period.

\* Not covered by the warranty are any damages resulting out of improper use, willful damage, normal wear-out (especially of the connectors) or connection with incompatible devices.

## 7.4. Manufacturer contact

Appsys ProAudio  
 Rolf Eichenseher  
 Bullingerstr. 63 / BK241  
 CH-8004 Zürich  
 Switzerland

[www.appsys.ch](http://www.appsys.ch)  
[info@appsys.ch](mailto:info@appsys.ch)  
 Phone: +41 43 537 28 51  
 Mobile: +41 76 747 07 42

## 7.5. Recycling



According to EU directive 2002/96/EU, electronic devices with a crossed-out dustbin may not be disposed into normal domestic waste. Please return the products back for environment-friendly recycling, we'll refund you the shipping fees.

## 7.6. Document Revision History

1: Initial release

## **7.7. About this document**

All trademarks mentioned in this document are property of the respective owners.  
All information provided here is subject to change without prior notice.

Document Revision: 1 · 2025-02-25

Copyright © 2025 Appsys ProAudio · Printed in Germany

IDENT 9.00.17476.00